

Ø.44 ~ THRU
(FIELD DRILLED)
(1)3/8-16 UNC X 3.50 LG HEX BOLT
(2)3/8 SAE FLAT WASHER
(1)3/8 LOCK WASHER
(1)3/8-16 UNC HEX JAM NUT

2 IN SCHED 40 PIPE
(Ø2.38 OD X Ø2.07 ID)


2 1/2 IN SCHED 40 PIPE
(Ø2.88 OD X Ø2.47 ID)

(3)3/8-16 UNC X 1.00 LG SQUARE HEAD SET SCREW AT 120°
(3)3/8-16 UNC HEX JAM NUT

R6.75

9.56

16.00



DRAWN: L. GRUNIS	10/3/2016
CHECKED:	
REVISION:	DATE:
APPROVED:	
QUOTE:	
S.O.#	
REF:	SCALE: NONE

UNITED LIGHTING STANDARDS
A DWH COMPANY

23171 Groesbeck Hwy.
Warren, MI 48089
P: (586) 774-5650 | F: (586) 774-5706
www.unitedlightingstandards.com

SOME GEOGRAPHICAL AREAS HAVE SPECIAL WIND CONDITIONS THAT CAN CREATE WIND INDUCED VIBRATIONS CAUSING A FATIGUE PROBLEM. NO METHOD HAS YET BEEN FOUND FOR PREDICTING DESTRUCTIVE LIGHTING POLE VIBRATION. THESE CONDITIONS ARE UNIQUE AND CANNOT BE GUARANTEED AGAINST, AND ARE THE RESPONSIBILITY OF A LOCAL SITE ENGINEER.		
TITLE:		
CATALOG:		
DWG NO: WB-15	SIZE: C	SHEET 1 OF 1